DECLARATION OF PERFORMANCE

According to Regulation (EU) n°305/2011

Unique identifier code for product-type / N° :: 58-RPC2006/07/03 Model :: FILIOFOCUS 2000 central vitré Intented uses of the product in accordance with the applicable harmonised technical specification :: Open fires fired by solid fuels Manufacturer :: Atelier Dominique Imbert s.a.s. 3 Impasse Claque Patin 34380 Viols le Fort Assessment and verification system for constancy of system 3 performance : Notified body : Rhein-Ruhr Feuerstättenorüfstelle Gmbh (RRF), N° 162: Test report number (based on System 3) : RRF – 29 10 2374 Declared performance : Harmonised technical specification : EN 13229:2002/A1:2003/A2:2005 Reaction to fire A1 Distance to combustible material Rear 80 cm Front // cm Front // cm Front // cm Risk of burning fuel falling out Pass Emissions of combustion products C0 Surface temperature (Nominal heat output) Pass Flue gas temperature (Nominal heat output) Surface temperature (Nominal heat output) Nether in the state output of the town o	0 0			
Intented uses of the product in accordance with the applicable harmonised technical specification : Manufacturer : Atelier Dominique Imbert s.a.s. 3 Impasse Claque Patin 34380 Viols le Fort Assessment and verification system for constancy of performance : Notified body : Test report number (based on System 3) : Ref – 29 10 2374 Declared performance : Harmonised technical specification : Reaction to fire A1 Distance to combustible material Rear Side Rear Front Front Front Floor Reas CO 0,08 % Dust CO 0,08 % Dust Surface temperature Pass Cleanability Pass Cleanability Pass Cleanability Pass Cleanability Pass Cleanability Pass Cleanability Pass Cleanability Pass Cleanability Pass Cleanability Pass Cleanability Pass Cleanability Pass Cleanability Pass Cleanability Pass Cleanability Pass Cleanability Pass Cleanability Pass Cleanability Pass Cleanability Pass Cleanability Pass Cleanability Pass Cleanability Pass Cleanability Pass Cleanability Pass Cleanability Pass Cleanability Pass Cleanability Pass Cleanability Pass Cleanability Pass Cleanability Pass Cleanability Pass Cleanability Pass Cleanability Pass Cleanability Pass Cleanability Pass Cleanability Pass Cleanability Pass Cleanability Pass Cleanability Pass Cleanability Pass Cleanability Pass Cleanability Pass Cleanability Pass Cleanability Pass Cleanability Pass Cleanability Pass Cleanability Pass Cleanability Pass Cleanability Pass Cleanability Pass Cleanability Pass Cleanability Pass Cleanability Pass Cleanability Pass Cleanability Pass Cleanability Pass Cleanability Pass Cleanability Pass Cleanability Pass Cleanability Pass Cleanability Pass Cleanability Pass Cleanability Pass Cleanability Pass Cleanability Pass Cleanability Pass Cleanability Pass Cleanability Pass Cleanability Pass Cleanability Pass Cleanability Pass Cleanability Pass Cleanability Pass Cleanability Pass Cleanabilit	Unique identifier code for product-type / N° :	58-RPC2006/07/03		
harmonised technical specification : Atelier Dominique Imbert s.a.s. Manufacturer : Atelier Dominique Imbert s.a.s. 3 Impasse Claque Patin 34380 Viols le Fort Assessment and verification system for constancy of performance : Notified body : Rhein-Ruhr Feuerstättenorüfstelle Gmbh (RRF), N° 162: Test report number (based on System 3) : RRF – 29 10 2374 Declared performance : Harmonised technical specification : EN 13229:2002/A1:2003/A2:2005 Reaction to fire A1 Distance to combustible material Rear 80 cm Front / cm Floor / cm Risk of burning fuel falling out Pass Emissions of combustion products CO 0,08 % Dust / mg/m ³ Surface temperature Pass Cleanability Pass Flue gas temperature (Nominal heat output) 244 °C Mechanical resistance (to carry a chimney/flue) NPD Nominal heat output 6 kW Room heating output - kW	Model :	FILIOFOCUS 2000 central vitré		
3 Impasse Claque Patin 34380 Viols le Fort Assessment and verification system for constancy of performance : System 3 Notified body : Test report number (based on System 3) : Rhein-Ruhr Feuerstättenorüfstelle Gmbh (RRF), N° 162: RRF – 29 10 2374 Declared performance : Harmonised technical specification : Reaction to fire EN 13229:2002/A1:2003/A2:2005 Reaction to fire A1 Distance to combustible material Rear 80 cm Front / cm Floor / cm Floor / mg/m³ Surface temperature Pass - Cleanability Pass - Flue gas temperature (Nominal heat output) Pass - Nominal heat output 6 kW		Open fires fired by solid fuels		
performance : Notified body : Test report number (based on System 3) : RRF – 29 10 2374 Declared performance : Harmonised technical specification : Reaction to fire Distance to combustible material Rear Side Rear Front Front Floor Risk of burning fuel falling out Emissions of combustion products CO 0,08 0,08 % Dust CO 0,08 % Dust (mg/m ³) Surface temperature Cleanability Flue gas temperature (Nominal heat output) NeD NeD Neg Neg Neg Rein-Ruhr Feuerstättenorüfstelle Gmbh (RRF), N° 162: RRF – 29 10 2374 RRF – 29 10 2374 RRF – 29 10 2374 RRF – 29 10 2374 Cm Flage stoperature (Nominal heat output) NPD Neg Neg Neg Neg Neg Neg Neg Neg	Manufacturer :	3 Impasse Claque Patin		
Test report number (based on System 3) : RRF – 29 10 2374 Declared performance : Image: Second System 3 (Second System 3) (Second Sys		System 3		
Harmonised technical specification :EN 13229:2002/A1:2003/A2:2005Reaction to fireA1Distance to combustible materialRear80cmSide80cmFront/cmFloor/cmRisk of burning fuel falling outPassEmissions of combustion productsCO0,08%Dust/mg/m³Surface temperaturePassCleanabilityPassFlue gas temperature (Nominal heat output)244°CMechanical resistance (to carry a chimney/flue)NPDNominal heat output6kWRoom heating output-kW			e Gmbh	(RRF), N° 162.
Reaction to fireA1Distance to combustible materialRear80cmSide80cmFront/cmFloor/cmRisk of burning fuel falling outPassEmissions of combustion productsCO0,08%Dust/mg/m³Surface temperaturePassCleanabilityPassFlue gas temperature (Nominal heat output)244°CMechanical resistance (to carry a chimney/flue)NPDNominal heat output6kWRoom heating output-kW	Declared performance :			
Reaction to fireA1Distance to combustible materialRear80cmSide80cmFront/cmFloor/cmRisk of burning fuel falling outPassEmissions of combustion productsCO0,08%Dust/mg/m³Surface temperaturePassCleanabilityPassFlue gas temperature (Nominal heat output)244°CMechanical resistance (to carry a chimney/flue)NPDNominal heat output6kWRoom heating output-kW	Harmonised technical specification :	EN 13229:2002/A1:2003/A2:200)5	
SideSide80cmFront/cmFloor/cmRisk of burning fuel falling outPassEmissions of combustion productsCO0,08%Dust/mg/m³Surface temperaturePassCleanabilityPassFlue gas temperature (Nominal heat output)244°CMechanical resistance (to carry a chimney/flue)NPDNominal heat output6kWRoom heating output-kW	Reaction to fire	A1		
Front/cmFloor/cmRisk of burning fuel falling outPassEmissions of combustion productsCO0,08Dust/mg/m³Surface temperaturePassCleanabilityPassFlue gas temperature (Nominal heat output)244YellYellMechanical resistance (to carry a chimney/flue)NPDNominal heat output6kWRoom heating output-	Distance to combustible material	Rear	80	cm
Floor/cmRisk of burning fuel falling outPassEmissions of combustion productsCO0,08%Dust/mg/m³Surface temperaturePassCleanabilityPassFlue gas temperature (Nominal heat output)244°CMechanical resistance (to carry a chimney/flue)NPDNominal heat output6kWRoom heating output-kW		Side	80	cm
Risk of burning fuel falling outPassEmissions of combustion productsCO0,08%Dust/mg/m³Surface temperaturePassCleanabilityPassFlue gas temperature (Nominal heat output)244°CMechanical resistance (to carry a chimney/flue)NPDNominal heat output6kWRoom heating output-kW		Front	/	cm
Emissions of combustion productsCO0,08%Dust/mg/m³Surface temperaturePassCleanabilityPassFlue gas temperature (Nominal heat output)244°CMechanical resistance (to carry a chimney/flue)NPDNominal heat output6kWRoom heating output-kW		Floor	/	cm
Dust/mg/m³Surface temperaturePassCleanabilityPassFlue gas temperature (Nominal heat output)244°CMechanical resistance (to carry a chimney/flue)NPDNominal heat output6kWRoom heating output-kW		Pass		
Surface temperature Pass Cleanability Pass Flue gas temperature (Nominal heat output) 244 °C Mechanical resistance (to carry a chimney/flue) NPD 6 kW Nominal heat output 6 kW Room heating output - kW	Emissions of combustion products	СО	0,08	%
Cleanability Pass Flue gas temperature (Nominal heat output) 244 °C Mechanical resistance (to carry a chimney/flue) NPD Nominal heat output 6 kW Room heating output - kW		Dust	/	mg/m ³
Flue gas temperature (Nominal heat output) 244 °C Mechanical resistance (to carry a chimney/flue) NPD 6 kW Nominal heat output 6 kW Room heating output - kW	Surface temperature	Pass		
Mechanical resistance (to carry a chimney/flue) NPD Nominal heat output 6 kW Room heating output - kW	Cleanability	Pass		
Nominal heat output6kWRoom heating output-kW	Flue gas temperature (Nominal heat output)		244	°C
Room heating output - kW		NPD		
			6	kW
Efficiency 50,0 %			-	kW
	Efficiency		50,0	%

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

<u>Laurent Gaborit</u> Directeur Général

Signature :

A

Viols le Fort, le 14 novembre 2019